

**VRLA / SLA Battery series** is designed with AGM Long life / Duration In High Performance Plate with Gain Extra Powder in Purify Electrolyte. Innovation Design of Fully Maintenance Free in Float Life 12 years. This is Highly Suited to Backup Applications in UPS/EPS, Security Alarm System, Deep Cycle Applications use in Telecom System and Solar System.

**Feature**

- Smart UPS Battery Design up to 10%
- Battery Capacity 100 Ah / 1700W - 15min
- AGM/SLA - Seal Lead Acid Battery
- Maintenance Free Battery Operation
- Non-Spillable Construction Design
- ABS container & Cover UL94HB-0
- Safety Value in explosion proof
- CE & UL Product Certification
- ISO9001 & ISO14001 Certified Factory

**Application**


- UPS & EPS
- Emergency System
- Communication Eq.
- Control Equipment
- Solar System
- Alarm System
- Medical Equipment
- Cable TV & CCTV




**Specifications**

Voltage Normal	: 12 VDC	in 6 Cell
Capacity @20Hr	: 106Ah @5.29A/	64W
@ 5Hr	: 84Ah @16.9A/	194W
@ 1Hr	: 62Ah @61.8A/	690W
@15min	: 39Ah @155 A/	1704W (*UPS)
@ 5min	: 22Ah @266 A/	2856W (*UPS)
Max. Discharge	: 1400A @14C	
Max. Charge Current	: 30A @0.3C	
Internal Resistance	: Apporx. 5 mΩ	Full Charge at 25°C
Design Float Life	: 12 years	at 25 °C
Cycle Lift Service	: 1500 cycles	at DOD 25%
Float Charge Voltage	: 13.5-13.8V	(-20mV/°C) at 25°C
Cycle Charge Voltage	: 14.4-15.0V	(-30mV/°C) at 25°C
Operation Temp.	: Normal 25+ / -3 °C	
	: Discharge -15 – 50 °C	
	: Charge -15 – 50 °C	
	: Storage -15 – 50 °C	
Self Discharge	: more than 6 Month	at 25°C
Terminal	: M6	
Container Material	: ABS UL94 HB-0	(Option :UL94V-0)
Physical	: 330x171x214mm – 30 Kgs	


**Dimension 330x171x214mm Weight = 30kgs @M6**




**Terminal Voltage (V) and Discharge Time**




Battery Voltage and Charge Time for Standby Use



Battery Voltage and Charge Time for Cycle Use



Cycle Service Life



**Constant Current(Amp) and Power (Watt/Box) Discharge Table**

Chuphotic.BRO-08.BATT EX12100-1700W 12V-100Ah.Rev1.10/2019

**VRLA-Battery Performance : %DOD, Constant Current, Constant Power (25°C / 10.2 F.V.)**

Discharge Time	5 Min	10Min	15Min	20Min	30Min	60Min	2Hr	3Hr	5Hr	10Hr	20Hr
%DOD	22%	32%	39%	42%	49%	62%	70%	81%	84%	100%	106%
Cons. Current	266A	195A	155A	126A	98A	61.8A	35A	27A	16.9A	10.0A	5.29A
Cons. Power	2856W	2148W	1704W	1386W	1104W	690W	402W	310W	194W	120W	64W